


MM8-2-SPOT RECESSED DOWNLIGHT ILLUMINATED MODULE

- Spot, Flood, and Wall Wash Beam Spreads
- 500lm (5W)



The ModuLED MM8 2-Spot recessed module allows downlighting to be spread out evenly and cleanly. This streamlined module will fit into any space giving it an all over refined look. This module is offered in variety of color temperatures and beam spreads.




Ordering Example: MM8B-B30-T30

MM8


Fixture	Finish	Beam Spread	CCT
Black	B	20° Spot	-B20
White	W	40° Flood	-B40
		Wall Wash	-WW

CCT
2700K, 90 CRI
3000K, 90 CRI
3500K, 90 CRI
4000K, 90 CRI

COMPATIBLE MOUNTING & POWER SUPPLIES¹



MTRFG
1.5" Recessed Flanged
Modular Slot
moduled.io/MTRFG



MTRTS
1.5" Recessed Trimless
Modular Slot
moduled.io/MTRTS



MTSRF
1.5" Surface
Modular Slot
moduled.io/MTSRF



MTPDN
1.5" Pendant
Modular Slot
moduled.io/MTPDN

¹Refer to Modular Slot Specification Sheets for more complete information.

Special order item. Extended lead time.

SPECIFICATION

Applications

The ModuLED MM8 2-Spot recessed module allows downlighting to be spread out evenly and cleanly. This streamlined module will fit into any space giving it an all over refined look. This module is offered in variety of color temperatures and beam spreads.

Housing

Polycarbonate, available in Black or White finish.

Mounting

Illuminated Module fits into Recessed Flanged (MTRFG), Recessed Trimless (MTRTS), Surface (MTSRF) and Pendant (MTPDN) modular Slot systems.

LED Details

Color Temperature - LEDs binned to 3-step MacAdam ellipses within the ANSI C78 377A standard for color temperature and chromaticity ranges light binning allowance. 90 CRI standard.

Lumen Maintenance - Minimum 50,000 hours L70 life based on ANSI TM-21 calculations from LM80 standardized test results.

Electrical Components

Driver - Highly efficient 24V DC with a power factor up to 0.99 making the product a perfect California Title 24 solution. 120V/277V AC for any residential or commercial applications.

Dimming - Superior PWM dimming technology compatible with many models of Triac, ELV, and 0-10V forward and reverse phase dimmers, and on/off switches. All models under 24V/96W are Class 2 compliant, making them safe and inspection-ready. They are derated, which means they can be loaded to maximum wattage capacity, with a minimum load of only 10%.

Certifications and Listings

ETL/cETL listed to UL1598 and UL8750. Suitable for dry and damp locations. NYC approved: Calendar #41937.

Warranty

Covered by a 5-Year Warranty to be free of defects in materials and craftsmanship. Recommended for applications where ambient temperatures do not exceed 35°C. Installations exceeding this temperature will result in reduced LED lamp life and a voided warranty.