


**PHOTOMETRY**

**MM2P06B (6" L, 1000lm, 11W, 15°)**

MM2P06B-P24-B15-T30		MULTIPLIERS	
<b>6", 1000lm, 15°, 3000K, CRI: 90</b>		<b>CCT</b>	
System Power (Watts)	9.8W	4000K : 1.07	
Test Date	5/20/2019	3500K : 1.00	
Beam Angle (50%)	19.6°	<b>3000K : 1.00</b>	
Field Angle (10%)	39.7°	2700K : 1.00	
Color Temperature	3161K		
CRI:	94.5		
R9 Value	63.3		
Lumens Delivered (lm)	1160.8		
CBCP	7153		
Volts:	24V DC		

**CANDELA TABULATION**



Maximum Candela = 7152.83 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1543	1720	3219
55	316	357	759
65	156	179	439
75	162	188	552
85	204	241	908

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	4.2'	49.4
16.0'	4.8'	36.3
18.0'	5.5'	27.8
20.0'	6.2'	22.0
22.0'	6.9'	17.8


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	3.2'	85.3
16.0'	3.9'	57.5
18.0'	4.5'	41.3
20.0'	5.2'	31.1
22.0'	5.9'	24.3


(fixture 4.8 ft below housing)



**MM2P06B (6" L, 1000lm, 11W, 40°)**

MM2P06B-P24-B40-T30		MULTIPLIERS	
<b>6", 1000lm, 40°, 3000K, CRI: 90</b>		<b>CCT</b>	
System Power (Watts)	9.8W	4000K : 1.07	
Test Date	5/20/2019	3500K : 1.00	
Beam Angle (50%)	41.1°	<b>3000K : 1.00</b>	
Field Angle (10%)	73.5°	2700K : 1.00	
Color Temperature	3111K		
CRI:	94.4		
R9 Value	62.5		
Lumens Delivered (lm)	1042.4		
CBCP	1898		
Volts:	24V DC		

**CANDELA TABULATION**



Maximum Candela = 1897.52 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5082	5666	10603
55	566	640	1360
65	166	190	467
75	174	203	595
85	194	229	865

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	9.0'	13.1
16.0'	10.5'	9.6
18.0'	12.0'	7.4
20.0'	13.5'	5.8
22.0'	15.0'	4.7


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	6.9'	22.6
16.0'	8.4'	15.3
18.0'	9.9'	11.0
20.0'	11.4'	8.3
22.0'	12.9'	6.4


(fixture 4.8 ft below housing)



**MM2P06B (6" L, 1000lm, 11W, 60°)**

MM2P06B-P24-B60-T30		MULTIPLIERS	
<b>6", 1000lm, 60°, 3000K, CRI: 90</b>		<b>CCT</b>	
System Power (Watts)	9.8W	4000K : 1.07	
Test Date	5/20/2019	3500K : 1.00	
Beam Angle (50%)	48.3°	<b>3000K : 1.00</b>	
Field Angle (10%)	80.8°	2700K : 1.00	
Color Temperature	3123K		
CRI:	94.5		
R9 Value	62.9		
Lumens Delivered (lm)	943.4		
CBCP	1365		
Volts:	24V DC		

**CANDELA TABULATION**



Maximum Candela = 1364.85 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6434	7174	13425
55	574	649	1379
65	133	152	373
75	151	176	517
85	129	153	576

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	10.8'	9.4
16.0'	12.6'	6.9
18.0'	14.4'	5.3
20.0'	16.2'	4.2
22.0'	18.0'	3.4


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	8.2'	16.3
16.0'	10.0'	11.0
18.0'	11.8'	7.9
20.0'	13.6'	5.9
22.0'	15.4'	4.6


(fixture 4.8 ft below housing)



**MM206B (6" L, 1000lm, 11W, 30° x 90°)**

MM2P06B-P24-B3090-T30		MULTIPLIERS	
<b>6", 1000lm, 30° x 90°, 3000K, CRI: 90</b>		<b>CCT</b>	
System Power (Watts)	9.8W	4000K : 1.07	
Test Date	5/14/2019	3500K : 1.00	
Vert. Beam Angle (50%) (W)	42.6°	<b>3000K : 1.00</b>	
Horiz'l Beam Angle (50%) (L)	82.6°	2700K : 1.00	
Vert. Field Angle (50%) (W)	78.4°		
Horiz'l Field Angle (50%) (L)	105.8°		
Color Temperature	3120K		
CRI:	94.4		
R9 Value	62.7		
Lumens Delivered (lm)	1128.6		
CBCP	1047		
Volts:	24V DC		

**CANDELA TABULATION**



Maximum Candela = 1047.19 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)  
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5079	26301	87833
55	653	3091	11565
65	166	271	862
75	162	179	494
85	178	192	653

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Distance Vert. Angle (50%) (W)	Beam Distance Hor. Angle (50%) (L)	Foot Candle (FC)
14.0'	9.4'	21.1'	7.2
16.0'	10.9'	24.6'	5.3
18.0'	12.5'	28.2'	4.1
20.0'	14.1'	31.7'	3.2
22.0'	15.6'	35.2'	2.6


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Distance Vert. Angle (50%) (W)	Beam Distance Hor. Angle (50%) (L)	Foot Candle (FC)
14.0'	7.1'	16.1'	12.5
16.0'	8.7'	19.6'	8.4
18.0'	10.3'	23.1'	6.0
20.0'	11.8'	26.6'	4.6
22.0'	13.4'	30.1'	3.6

(fixture 4.8 ft below housing)



2019.06.13


**PHOTOMETRY**

**MM2P12B (12" L, 2000lm, 22W, 15°)**

MM2P12B-P24-B15-T30	
<b>12", 2000lm, 15°, 3000K, CRI: 90</b>	
System Power (Watts)	17.5W
Test Date	5/20/2019
Beam Angle (50%)	19.9°
Field Angle (10%)	41.0°
Color Temperature	3161K
CRI:	94.5
R9 Value	63.3
Lumens Delivered (lm)	2250.5
CBCP	13274
Volts:	24V DC

MULTIPLIERS	
<b>CCT</b>	
4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 13274.45 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)


LUMINANCE DATA (cd/sq.m)			
Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1399	1638	3337
55	327	391	936
65	198	241	703
75	228	284	1079
85	263	336	1948

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
12.0'	3.5'	132.0
14.0'	4.2'	91.7
18.0'	5.6'	51.7
20.0'	6.3'	40.8
24.0'	7.7'	27.4


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
12.0'	2.5'	259.2
14.0'	3.2'	158.4
18.0'	4.6'	76.7
20.0'	5.3'	57.8
24.0'	6.7'	36.2

(fixture 4.8 ft below housing)




**MM2P12B (12" L, 2000lm, 22W, 40°)**

MM2P12B-P24-B40-T30	
<b>12", 2000lm, 40°, 3000K, CRI: 90</b>	
System Power (Watts)	17.5W
Test Date	5/20/2019
Beam Angle (50%)	41.0°
Field Angle (10%)	73.1°
Color Temperature	3111K
CRI:	94.4
R9 Value	62.5
Lumens Delivered (lm)	1779.5
CBCP	3268
Volts:	24V DC

MULTIPLIERS	
<b>CCT</b>	
4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 3268.12 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)


LUMINANCE DATA (cd/sq.m)			
Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4228	4948	10082
55	444	531	1272
65	161	197	573
75	175	218	828
85	196	251	1454

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
12.0'	7.5'	32.5
14.0'	9.0'	22.6
18.0'	12.0'	12.7
20.0'	13.5'	10.1
24.0'	16.5'	6.7


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
12.0'	5.4'	63.8
14.0'	6.8'	39.0
18.0'	9.8'	18.9
20.0'	11.3'	14.2
24.0'	14.3'	8.9

(fixture 4.8 ft below housing)




**MM2P12B (12" L, 2000lm, 22W, 60°)**

MM2P12B-P24-B60-T30	
<b>12", 2000lm, 60°, 3000K, CRI: 90</b>	
System Power (Watts)	17.5W
Test Date	5/20/2019
Beam Angle (50%)	48.3°
Field Angle (10%)	80.8°
Color Temperature	3123K
CRI:	94.5
R9 Value	62.9
Lumens Delivered (lm)	1924.1
CBCP	2777
Volts:	24V DC

MULTIPLIERS	
<b>CCT</b>	
4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 2776.53 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)


LUMINANCE DATA (cd/sq.m)			
Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6661	7796	15885
55	569	680	1630
65	186	227	662
75	198	247	936
85	229	293	1696

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
12.0'	9.0'	27.6
14.0'	10.8'	19.2
18.0'	14.4'	10.8
20.0'	16.2'	8.5
24.0'	19.8'	5.7


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
12.0'	6.4'	54.2
14.0'	8.2'	33.1
18.0'	11.8'	16.0
20.0'	13.6'	12.1
24.0'	17.2'	7.6

(fixture 4.8 ft below housing)




**MM2P12B (12" L, 2000lm, 22W, 30° x 90°)**

MM2P12B-P24-B3090-T30	
<b>12", 2000lm, 30°x90°, 3000K, CRI: 90</b>	
System Power (Watts)	17.5W
Test Date	5/20/2019
Vert. Beam Angle (50%) (W)	42.6°
Horiz'l Beam Angle (50%) (L)	82.6°
Vert. Field Angle (50%) (W)	78.3°
Horiz'l Field Angle (50%) (L)	105.8°
Color Temperature	3120K
CRI:	94.4
R9 Value	62.7
Lumens Delivered (lm)	2257.3
CBCP	2097
Volts:	24V DC

MULTIPLIERS	
<b>CCT</b>	
4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 2094.38 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)  
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)


LUMINANCE DATA (cd/sq.m)			
Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5050	27442	99787
55	649	3246	13708
65	165	286	1083
75	160	190	682
85	176	205	1073

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Distance Vert. Beam Angle (50%) (W)	Beam Distance Hor. Beam Angle (50%) (L)	Foot Candle (FC)
12.0'	7.8'	17.6'	20.8
14.0'	9.4'	21.1'	14.5
18.0'	12.5'	28.2'	8.2
20.0'	14.1'	31.7'	6.5
24.0'	17.2'	38.7'	4.3


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Distance Vert. Beam Angle (50%) (W)	Beam Distance Hor. Beam Angle (50%) (L)	Foot Candle (FC)
12.0'	5.6'	12.6'	41.0
14.0'	7.1'	16.1'	25.0
18.0'	10.3'	23.1'	12.1
20.0'	11.8'	26.6'	9.1
24.0'	14.9'	33.7'	5.7

(fixture 4.8 ft below housing)



2019.06.13

**PHOTOMETRY**

**MM2P18B (18" L, 3000lm, 33W, 15°)**

**MM2P18B-P24-B15-T30**

**18", 3000lm, 15°, 3000K, CRI: 90**


System Power (Watts)	29.8W
Test Date	5/20/2019
Beam Angle (50%)	19.6°
Field Angle (10%)	39.7°
Color Temperature	3161K
CRI:	94.5
R9 Value	63.3
Lumens Delivered (lm)	3482.6
CBCP	21459
Volts:	24V DC

**MULTIPLIERS**

**CCT**

4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 21458.5 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1533	1824	3836
55	314	382	960
65	155	193	604
75	161	206	872
85	202	265	1911

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	4.2'	148.3
16.0'	4.8'	109.0
20.0'	6.2'	66.0
24.0'	7.6'	44.2
28.0'	9.0'	31.7


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	3.2'	256.0
16.0'	3.9'	172.4
20.0'	5.2'	93.4
24.0'	6.6'	58.5
28.0'	8.0'	40.0

(fixture 4.8 ft below housing)



**MM2P18B (18" L, 3000lm, 33W, 40°)**

**MM2P18B-P24-B40-T30**

**18", 3000lm, 40°, 3000K, CRI: 90**


System Power (Watts)	29.8W
Test Date	5/20/2019
Beam Angle (50%)	41.1°
Field Angle (10%)	73.5°
Color Temperature	3111K
CRI:	94.4
R9 Value	62.5
Lumens Delivered (lm)	3127.1
CBCP	5693
Volts:	24V DC

**MULTIPLIERS**

**CCT**

4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 5692.57 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5049	6007	12634
55	562	685	1720
65	165	206	644
75	173	221	936
85	192	252	1820

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	9.0'	39.3
16.0'	10.5'	28.9
20.0'	13.5'	17.5
24.0'	16.5'	11.7
28.0'	19.5'	8.4


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	6.9'	67.9
16.0'	8.4'	45.7
20.0'	11.4'	24.8
24.0'	14.4'	15.5
28.0'	17.4'	10.6

(fixture 4.8 ft below housing)



**MM2P18B (18" L, 3000lm, 33W, 60°)**

**MM218B-B60-T30**

**18", 3000lm, 60°, 3000K, CRI: 90**


System Power (Watts)	29.8W
Test Date	5/17/2019
Beam Angle (50%)	48.3°
Field Angle (10%)	80.8°
Color Temperature	3123K
CRI:	94.5
R9 Value	62.9
Lumens Delivered (lm)	3830.4
CBCP	4095
Volts:	24V DC

**MULTIPLIERS**

**CCT**

4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 4094.56 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6392	7605	15996
55	571	695	1745
65	131	164	512
75	151	193	817
85	128	168	1212

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	10.8'	28.3
16.0'	12.6'	20.8
20.0'	16.2'	12.6
24.0'	19.8'	8.4
28.0'	23.3'	6.0


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Dia. (D)	Foot Candle (FC)
14.0'	8.2'	48.9
16.0'	10.0'	32.9
20.0'	13.6'	17.8
24.0'	17.2'	11.2
28.0'	20.8'	7.6

(fixture 4.8 ft below housing)



**MM218B (18" L, 3000lm, 33W, 30° x 90°)**

**MM2P18B-P24-B3090-T30**

**18", 3000lm, 30°x90°, 3000K, CRI: 90**


System Power (Watts)	29.8W
Test Date	5/20/2019
Vert. Beam Angle (50%) (W)	42.6°
Horiz'l Beam Angle (50%) (L)	82.6°
Vert. Field Angle (50%) (W)	78.4°
Horiz'l Field Angle (50%) (L)	105.8°
Color Temperature	3120K
CRI:	94.4
R9 Value	62.7
Lumens Delivered (lm)	3386.1
CBCP	3142
Volts:	24V DC

**MULTIPLIERS**

**CCT**

4000K :	1.07
3500K :	1.00
<b>3000K :</b>	<b>1.00</b>
2700K :	1.00

**CANDELA TABULATION**



Maximum Candela = 3141.57 Located At Horizontal Angle = 0, Vertical Angle = 0  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)  
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)

**LUMINANCE DATA (cd/sq.m)**


Angle in Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5046	27880	104653
55	649	3306	14626
65	165	292	1186
75	160	194	780
85	177	211	1372

**FOOTCANDLE DISTRIBUTION**

**Recessed Track (MTRFG, MTRTS)**

Ceiling HT FT (H)	Beam Distance	Foot Candle (FC)	
	Vert. Beam Angle (50%) (W)	Hor. Beam Angle (50%) (L)	
14.0'	9.4'	21.1'	21.7
16.0'	10.9'	24.6'	16.0
20.0'	14.1'	31.7'	9.7
24.0'	17.2'	38.7'	6.5
28.0'	20.3'	45.7'	4.6


(fixture 2.0 ft below housing)



**Pendant Track (MTPDN) with 32" cable**

Ceiling HT FT (H)	Beam Distance	Foot Candle (FC)	
	Vert. Beam Angle (50%) (W)	Hor. Beam Angle (50%) (L)	
14.0'	7.1'	16.1'	37.5
16.0'	8.7'	19.6'	25.2
20.0'	11.8'	26.6'	13.7
24.0'	14.9'	33.7'	8.6
28.0'	18.1'	40.7'	5.9

(fixture 4.8 ft below housing)



2019.06.13